

TECHNICAL DATA SHEET

RUSTOVEL A114

FLASH POINT

>180 °C

SALT SPRAY TEST

>24 hours

VISCOSITY 40 °C

2-4 cSt

DENSITY 15 °C

0.88 kg/l

DESCRIPTION

RUSTOVEAL A114 is corrosion preventive and antirust non-washable oil, Provides outstanding rust protection for 12month. It can be removed by washing with solvent.

FEATURES AND BENEFITS

Spread ability

- Highly penetrate and spread ability covering large areas.

Film stability

- Thixotropic property of the oil with high film stability.

Resistance to Water

- Excellent resistance to water washout and Spray-off.

Anti wear properties

- Anti-wear properties provide protection against premature wear.

Corrosion Resistance

- High corrosion inhibiting properties to protect components saved under very humid environment.

Resistance to Oxidation

- The use of a premium antioxidant ensures excellent thermal and oxidation stability.

APPLICATION AREAS

Steel sheets, Equipments, Tools.

TYPICAL DATA

TEST	RESULT
Colour	Yellowish brown
PH	6-7
Kinematic Viscosuty@40°C	2-4 cSt
Density at 15 °C, ASTM D 1298	0.88 kg/l
Flash Point	>180 °C
Rust test, ASTM D665 B (SALT WATER)	Pass
Salt spray test, ASTM B 117	>24 hours